

# 27.9W StarT10

Type B LED 4' Tube

NEW

## Applications

Automotive | Industrial | Office | Petroleum | Retail & Grocery

## Performance Summary

**Delivered Lumens:** 4,150 - 4,550 L

**Input Power:** 27.9W

**Efficacy:** 149 - 163L/W

**Lifetime\*:** >200,000 hours

**CRI:** 80 min

**CCT:** 3500K, 4000K, 5000K

**Input Voltage:** 120 - 277V

**Environmental Rating:** Damp

**Dimming:** Non-dimmable

**Tube Material:** Polycarbonate with clear or frosted lens

**Power Locations:** Single or double ended

**Compliance:** UL 1598 Type B LED lamp (integrated driver)

**Operating Temp:** -40 to 30°C

**Warranty:** 10-Years

**DesignLights Consortium Listed**

## Fixtures

Part Number	CCT	Power Locations	Frosted Lens		
			Lumens	Wattage	L/W
ST1-1-UNV-4-27B-35	3500K	Single Ended	4,150	27.9	149
ST1-1-UNV-4-27B-40	4000K	Single Ended	4,200	27.9	151
ST1-1-UNV-4-27B-50	5000K	Single Ended	4,250	27.9	152
ST1-1-UNV-4-27B-35-DE	3500K	Double Ended	4,150	27.9	149
ST1-1-UNV-4-27B-40-DE	4000K	Double Ended	4,200	27.9	151
ST1-1-UNV-4-27B-50-DE	5000K	Double Ended	4,250	27.9	152

Part Number	CCT	Power Locations	Clear Lens		
			Lumens	Wattage	L/W
ST1-1-UNV-4-27B-35-C	3500K	Single Ended	4,450	27.9	159
ST1-1-UNV-4-27B-40-C	4000K	Single Ended	4,500	27.9	161
ST1-1-UNV-4-27B-50-C	5000K	Single Ended	4,550	27.9	163
ST1-1-UNV-4-27B-35-C-DE	3500K	Double Ended	4,450	27.9	159
ST1-1-UNV-4-27B-40-C-DE	4000K	Double Ended	4,500	27.9	161
ST1-1-UNV-4-27B-50-C-DE	5000K	Double Ended	4,550	27.9	163



Frosted Lens

Clear Lens



## Accessories

### Housing

Part Number	Description
LS-1-4	LoneStar   1-Tube 4' Strip
LS-2-4	LoneStar Tandem   2-Tube 8' Strip
TWS1	TwinStar   2-Tube 4' Strip
TWS1-T	TwinStar Tandem   4-Tube 8' Strip
TWS1-1	TwinStar   2-Tube 4' Strip   OCC Ready
TR-3-4	TriStar   3-Tube 4' Strip
USQS-44	QuadStar   4-Tube 4' Wide Body Strip
HBT1	SixShooter   6-Tube High Bay Housing
HBT1-1	SixShooter   6-Tube High Bay Housing w/ OCC Accommodations
UCLL-24	2x4 Housing   Ceiling Mounted
UCLLS-24	2x4 Housing   Surface Mounted
LS-WG-48	Wireguard for LoneStar
BCK-8-2-US	1x8 2-Lamp Retrofit
BCK-8-4-US	1x8 4-Lamp Retrofit
RKSR-232TAN-WINST	8' to 4' Conversion Kit
USVT-24	4' VaporTight
USVT-44	8' VaporTight

### Battery Backup

Part Number	Description
IIS-35-I	IOTA Emergency Driver

### Occupancy Sensor

Part Number	Description
LSXR-610-42L	On/Off   120-277V   White

## Specifications

<b>Dimensions (L x Diameter):</b>	48.0" x 1.25"
<b>Net Weight:</b>	0.75 lbs.

\*Product "Lifetimes" refer only to the LED light engine, not the power source, and are based on the Illuminating Engineering Society's TM21 Projected Lumen Maintenance methodology at a 25°C/77°F ambient temperature. The lifetimes are solely meant to be a guide for expected LED degradation and not a warranty or predictive of their actual life, which can be affected by ambient temperatures and other factors.