National LED

Aero Champion

LED RGB Sports Lighting



Key Features

- · Combines superior performance and advanced thermal management in an appealing design.
- · Versatile mounting options provide operational flexibility for any outdoor installation.
- · Additional intelligent lighting controls and monitoring capabilities available.

Electrical

- 277-480V available.
- 0-10V dimming standard.
- Operating temperature: -40°C to 50°C (-40°F to 122°F).

Mounting

· Trunnion mount, universalmount, or adjustable slip fitter mount available.

Construction

- Rugged die-cast aluminum design protects integral components from harsh environments and optimizes thermal management.
- · Housing is protected by a corrosion resistant powder coat finish.
- IP66 rated optics offer protection from outdoor conditions.

Optics

- Industry-leading RGB LEDs (Red/Green/Blue).
- Available Beam Angles: 15°, 20°, 35°, & 55°
- Lumen Maintenance: ≥50,000 Hours (L70). ¹

Warranty

· Backed by National LED's Five-Year Warranty.

Project	Date
---------	------

Catalog Number	Туре
3	- 7

PCLS RGB Lumen Outputs					
LED Type	Lumen Output				
Red LEDs	4,388				
Blue LEDs	2,231				
Green LEDs	31,838				
White LEDs	25,610				

Product Overview

The Aero Champion RGB sports & flood light will give you the game-changing performance you need to professionally illuminate any sports venue. With multiple beam angles and mounting options, you'll get the light exactly where it's needed the most - right in the middle of the action! If you are ready for the next level of athletic performance, there are additional intelligent lighting controls available.

Product Applications

- University Arenas
- Collegiate Arenas
- Pro Arenas
- Sports Fields
- Tennis Courts
- Gymnasiums
- Field Houses
- Recreation Areas
- · High Mast Lighting
- Security Lighting

- UL Listed
- Complies with UL1598 and CSA C22.2
- Suitable for Wet Locations (IP66 Rated)
- RoHS Compliant





Product Certifications







Example: AC-800-UNVH-RGB-BK-Z1-55

Ordering Information

AC		800										
Ser	ies	Model	Input Voltage		ССТ	F	Finish		Mounting		Beam Angle	
			UNVH	277-480V	RGB ² RGB/RGBW	BK	Black	Z 1	Trunnion	15	15°	
								Z2	Universal	20	20°	
									Mount	35	35°	


Slip Fitter Pole Mount Accessories Light Shield/Visor Aiming Laser Wireless Control Casambi-Enabled DMX Control


Aero Champion

LED Sports Lighting

Dimensions

Net Weight	EPA Rating			
49.05 lbs. [22.25kg]	2.0 ft. ²			





National LED

Optical Performance Data

AC 800W RGB Lumen Outputs						
LED Type	Wattage	Lumen Output				
Red LEDs	219.3W	4,388.7				
Blue LEDs	200.0W	2,231.0				
Green LEDs	207.9W	31,838.0				
White LEDs	189.3W	25,610.3				

- RGB intensely saturated color light (Red/Green/Blue).
- 800W total output (nominal wattage).
- Available beam angles: 15-20° (NEMA2 Narrow), 35° (NEMA3 Medium Narrow), 55° (NEMA4 Medium)

Mounting & Accessories

Light Shielf/Visor [SH]



Trunnion Mount [Z1]



Universal Mount [Z2]



Adjustable Slip Fitter Pole Mount [Z3]

