




White LED



RGB LED



Specifications

Construction

- Sturdy aluminum die-cast body finished with durable powder coating.

Performance

- Available in single CCT options (4000K, 5000K, 5700K) with CRI > 70, or in RGB (Red, Green, Blue).
- Optional beam distributions: NEMA 3H3V, NEMA 4H4V, and NEMA 5H5V.

Electrical

- 0–10V dimmable driver with internal dimming wire (no external lead).
- Input voltage range: AC120–277V / AC200–480V (50/60Hz), equipped with a standard 20KV surge protector.
- Includes a 3 ft. (35.4") power cord for simplified installation.

Controls

- RGB LED model supports control via DALI-2 and D4i.
- White LED model (120–277Vac) supports 0–10V dimming only.
- White LED model (200–480Vac) supports 0–10V dimming, DALI-2, and D4i.

Warranty

- 10-year limited warranty.

Mounting

- Yoke mount and pendant mount

Finish

- Black is standard.



Black

Certification

- cULus Listed and DLC 5.1 Premium Pending

Ambient Temperature

- 40° F (-40° C) to 122° F (50° C)

Life Span

- 100,000 hour lifespan.

ORDERING GUIDE

Example: SPL 800 LV 40 BK 33 P

Fixture Type	Wattage	Voltage	CCT	Finish	Dist. Type YY	Mounting
SPSL Sports Light	800 800W 600 600W 480 480W	LV 120-277V HV1 200-480V (White LED) HV2 277-480V (RGB LED)	40 4000K 50 5000K 57 5700K RGB RGB	BK Black	33 3H3V 44 4H4V 55 5H5V	P Pendant Mount YK Yoke Mount

SPSL

www.NationalLED.com | 281-636-5095

Due to continued product improvements, product specifications are subject to change without notice. Please visit www.NationalLED.com for the most updated product specifications.